

Hush Cupboard Sliding Door Gear

A TOP HUNG DOOR GEAR FOR LIGHT-WEIGHT CUPBOARD DOORS

APPLICATION

Quiet top hung system, single or multiple track runs.

RANGE

Maximum door weight 9kg (20lb).

DOOR CONSTRUCTION

Door thickness 12 to 20mm, usually solid. Width of door not less than half height.

FIXING

Top track soffit fixed. Individual tracks allow for variation of door thickness. Bottom guides may be recessed or proud. Position sliders near edge of door.

TOP TRACK

13-2 Extruded Aluminium drilled for soffit fixing. Lengths 1.2m and 1.8m.

TOP SLIDERS, BOTTOM GUIDES AND DOOR STOP

Nylon, with woodscrews for fixing.

FINGER PULLS

95-611 white plastic, size 32mm diameter, 8mm deep.

STANDARD TRACKSETS

SET 4 Z – For two doors within 1.2m opening.

SET 6 Z – For two doors within 1.8m opening.

Contents per set: all sliders, top track, bottom guides, door stop, finger pulls and all screws for two doors on parallel tracks.

TWO DOOR COMPONENT PACK 2 Z

Comprising all necessary sliders, guides, finger pulls, door stops and screws for hanging two doors.

TOP TRACK

Available in 1.2m and 1.8m lengths.

