

Double 60X Wardrobe Sliding Door Gear

FOR EXTRA THICK DOORS OPERATING ON A ONE-PIECE DOUBLE TOP TRACK

APPLICATION

For wardrobes and cupboards using standard flush doors of light weight construction.

RANGE

- Maximum door weight 27kg (60lb).
- Maximum door height 2m (6ft 6ins).
- Maximum door width 1m (3ft 3ins).

DOOR CONSTRUCTION

Door thickness between 36 to 44mm. Minimum frame width 30mm to accommodate hanger aprons. Door width should not be less than one quarter height. Recommended handle height two thirds from bottom of door for best results.

FIXING

Soffit fixed, one piece double top track. Fixed track centres need adjustable gaps between doors. Bottom guides recessed or proud. Position hangers close to edge of doors.

HANGERS

Nylon wheels, ground steel axles, plated steel adjustable aprons.

TOP TRACK

Aluminium drilled for soffit fixing.

BOTTOM GUIDES

Nylon, woodscrew fixing.

DOOR STOP

97-728 Nylon.

FINGER PULL

95-611 White plastic, size 32mm diameter, 8mm deep.

STANDARD TRACKSETS

SET 4DX – For two doors within 1.2m opening.

SET 5DX – For two doors within 1.5m opening.

SET 6DX – For two doors within 1.8m opening.

SET 8DX – For three doors within 2.4m opening.

Contents per set: 1 length of double one-piece aluminium top track, door hangers, nylon guides, finger pulls, door stops and all screws.

SINGLE DOOR COMPONENT PACK 1 TD

Comprising all necessary hangers, guides, finger pulls, door stop and screws for one door.

