

# Straightaway 660 Bottom Rolling Door Gear

## FOR DOORS ON SINGLE AND MULTIPLE PARALLEL TRACK RUNS

### APPLICATION

For internal bottom rolling doors for wardrobes, cupboards, etc. Single or multiple runs of track.

### RANGE

- Maximum door weight 55kg (120lb).
- Maximum door height 2.1m (7ft).

The area of a single door should be related to all other factors.

### DOOR CONSTRUCTION

Door thickness 30 to 45mm. Width one third height minimum, handle height three fifths from bottom for best results.

### FIXING

Top channel soffit fixed. Floor tracks recessed or surface mounted. Mortice rollers suit 30mm doors minimum.

### BOTTOM ROLLERS

66-401 Mortice fixing. Steel casing zinc plated, nylon wheels, ground steel axles.

### BOTTOM TRACKS

66-1 Steel, 66-3 or 70-3 Brass. Drilled and c/sk for woodscrews. Lengths 1.8m to 3.0m.

### TOP GUIDES

42-374 Nylon, edge fixing.

### TOP GUIDE CHANNEL

42-1 Galvanised steel. Drilled and c/sk for woodscrews. Lengths 1.8m to 3.0m.

### FURNITURE

Full range of door furniture shown on page 3.

### FINISHES

Bottom roller casing plated, steel track and channel galvanised, furniture usually satin anodised.

### FIXING SCREWS

Included for all track and fittings.

