

Straightaway 700 Bottom Rolling Door Gear

FOR STRAIGHT SLIDING DOORS AND WINDOWS

APPLICATION

Bottom rolling straight sliding heavy duty cupboard doors, timber patio doors and windows.

RANGE

- Maximum door weight 115kg (250lb).
- Maximum door height 2.4m (8ft).

The area of a single sliding leaf should be related to all other factors.

DOOR CONSTRUCTION

Door thickness 30 to 60mm, width one third height minimum, handle height three fifths from bottom for best results. When fully open the sliding panel should project a minimum of 65mm to avoid fingers becoming trapped between handle and fixed panel. Bottom rail should be of sufficient depth to house roller casing.

FIXING

Top guide track soffit fixed. Floor track may be recessed or proud. Mortice for bottom rollers must fit tight around roller casing and weight of sliding door carried on top of casing above wheel.

BOTTOM ROLLERS

64-402 Bottom roller for 64-3 track, 70-402 Bottom roller for 66-1, 66-3 and 70-3 tracks. Die cast casings, nylon wheels with needle bearings.

BOTTOM TRACKS

66-1 steel, 66-3, 64-3 and 70-3 Brass. Drilled and c/sk for woodscrews. Lengths 1.8m to 3.0m.

TOP GUIDES

44-362 Aluminium rattleproof top guides with brush welt, two screw fixing.

TOP CHANNEL

44-2 Aluminium or 44-3 Brass. Drilled and c/sk for woodscrews. Lengths 1.8m to 3.0m.

FURNITURE

Full range of door furniture shown on page 3.

FINISHES

Aluminium and brass tracks self-colour. Straightaway 700 is also available in a range of stainless steel components. Details available on request.

