

Twin 60 & Single 60 Wardrobe Sliding Door Gear

FOR CUPBOARD OR WARDROBE DOORS

APPLICATION

Top hung system for wardrobes, cupboards and similar doors, single or multiple runs of track. Light domestic use, normal handling.

RANGE

- Maximum door weight 27kg (60lb).
- Maximum door height 2m (6ft 6ins).
- Maximum door width 1m (3ft 3ins).

DOOR CONSTRUCTION

Door thickness 16 to 40mm. Frame width 30mm minimum to accommodate hanger aprons. Door width one quarter height minimum, handle height two thirds from bottom for best results.

FIXING

Top track soffit fixed. Individual tracks allow for variation of door thickness. Guides at floor level recessed or proud. Position hanger close to edge of doors.

HANGERS

Nylon wheels, ground steel axles, plated steel adjustable aprons.

TOP TRACK

23-2 Aluminium drilled for soffit fixing. Lengths 1.2m to 2.4m.

BOTTOM GUIDES

Nylon, woodscrew fixing.

DOOR STOP

97-728 Nylon.

FINGER PULL

95-611 White plastic, size 32mm diameter, 8mm deep.

STANDARD TRACKSETS

SINGLE 60

SET 4S – For one door - 600mm opening.

SET 5S – For one door - 750mm opening.

SET 6S – For one door - 900mm opening.

Contents per set: 1 length of top track, 2 hangers, nylon guides, finger pull and all screws.

TWIN 60

SET 4T – For two doors within 1.2m opening.

SET 5T – For two doors within 1.5m opening.

SET 6T – For two doors within 1.8m opening.

SET 8T – For three doors within 2.4m opening.

Contents per set: 2 lengths of top track, hangers, nylon guides, finger pulls, door stops and all screws.

SINGLE DOOR COMPONENT PACK 1TD

Comprising all necessary hangers, guides, finger pull, door stop and screws for one door.

TOP TRACK

Available in 1.2, 1.5, 1.8 and 2.4m lengths.

