

Twin 100 Wardrobe Sliding Door Gear

WITH TWIN PARALLEL TRACKS

APPLICATION

Top hung system for wardrobes, cupboards and similar doors. Single or multiple runs of track. Heavy public use.

RANGE

- Maximum door weight 45kg (100lb).
- Maximum door height 2.1m (7ft).
- Maximum door width 1.2m (4ft).

DOOR CONSTRUCTION

Door thickness 20 to 40mm. Frame width 38mm minimum to accommodate hanger aprons. Door width quarter height minimum, handle height two thirds from bottom for best results.

FIXING

Top track soffit fixed. Individual tracks allow for variation of door thickness. Guides at floor level recessed or proud. On treble track installations floor channel should be used as shown. Position hangers close to edge of door.

HANGERS

Nylon wheels, ground steel axles, plated steel adjustable aprons.

TOP TRACK

26-2 Aluminium, drilled for soffit fixing. Lengths 1.8m and 2.4m.

BOTTOM GUIDES

Nylon fixed with woodscrews.

ALTERNATIVE BOTTOM GUIDING

Groove bottom of door for 42-1 Channel and position 42-371 Nylon guide at centre of door travel.

DOOR STOP

97-726 Nylon with rubber buffer.

HANDLE

95-617 Flush handle size 100 x 50mm.

STANDARD TRACKSETS

SET 6H – For two doors within 1.8m opening.

SET 8H – For three doors (2 front, 1 rear) within 2.4m opening.

Contents per set: 2 lengths of top track, hangers, nylon guides, door stop & all screws for doors on parallel tracks.

SINGLE DOOR COMPONENT PACK 1H

Comprising all necessary hangers, guides, door stop and screws for one front door or Single 100 application. Rear door components available on request.

TOP TRACK

Available in 1.8m and 2.4m lengths.

