

# Twin-Fold Folding Door Gear

## FOR CUPBOARDS, WARDROBES, RECESSES ETC.

### APPLICATION

Folding door system for built-in storage units where maximum access is required. Not suitable for rebated head or cill.

### RANGE

- Maximum door weight 15kg (30lb).
  - Maximum door height 2.4m (8ft).
  - Maximum door leaf width 450mm (1ft 6ins).
- Hung in pairs, only 2, 4, 6 or 8 door leaves per opening.

### DOOR CONSTRUCTION

Door thickness 20 to 35mm. All widths equal, refer to drawing for calculations.

### FIXING

Top track soffit fixed. All fittings concealed from outside. Lateral and vertical adjustment with pivots.

### TOP TRACK

Aluminium decorative finish one side d/c/sk for wood. Lengths 775mm and 930mm.

### TOP PIVOT SOCKET SLIDE

Nylon, adjustable.

### TOP PIVOT

Steel, spring loaded.

### BOTTOM PIVOT

Steel, vertically adjustable.

### BOTTOM PIVOT SOCKET SLIDE

Steel housing nylon socket laterally adjustable.

### TOP ROLLER GUIDE

Steel, nylon roller spring loaded.

### HINGES

Steel, zinc plated.

### FURNITURE

Stops, pulls and alignment plates included.

### FIXING SCREWS

Included for track and all fittings.

### STANDARD TRACKSETS

SET TF 36/2 – 2 Doors, 900mm opening.

SET TF 60/4 – 4 Doors, 1.5m opening.

Contents per set: top track, top and bottom pivots, top guide, hinges, stop, handle and spanner.

Combinations of two - 2 door sets, one - 2 door set and one - 4 door set or two - 4 door sets may be used.

